



DC TWO

PERFEKTER SCHNITT - Die perfekte Extraktion beginnt mit dem perfekten Schnitt. Die exklusiven 65 mm Mahlscheiben, speziell für die Espressoermahlung entwickelt, garantieren eine konstante Partikelgrößenverteilung.

TEMPERATUR - Automatisches Kühlsystem und Sensormessung an zwei Punkten schützen das Kaffeemehl und die Mahlscheiben vor Überhitzung.

EXAKTHEIT - Elektronische Mahlgradverstellung und eine spezielle Aufhängung ermöglichen größtmögliche Parallelität der Mahlscheiben – Reduktion von Dosierschwankungen.

BEDIENBARKEIT - Unterschiedliche Parameter an beiden Mahlgruppen: die dc two kann unabhängig von den Mahlgruppen im manuellen oder angebundendem Modus angewendet werden (GCS, Grinder Control System).

dimensionen (L x h x t)	319x630x300 mm
gewicht	21 kg
mahlleistung	ca. 4 g/sek
trichterinhalt	2 x 1000 g
leistungsaufnahme	800 W
anschlusswerte	230/240 V, 115 V
umdrehungen/min.	1350 (200 V - 50 Hz) U/min
mahlscheiben ø	65 mm



WHITE OAK

1-GR-DC-TWO-2-WO-230



DARK WALNUT

1-GR-DC-TWO-2-DN-230



DYNAMIC WHITE

1-GR-DC-TWO-2-W-230



TOTAL WHITE

1-GR-DC-TWO-2-X-230



DYNAMIC GREY

1-GR-DC-TWO-2-DG-230



TOTAL GREY

1-GR-DC-TWO-2-TG-230



DYNAMIC RED

1-GR-DC-TWO-2-DR-230



TOTAL RED

1-GR-DC-TWO-2-TR-230



DYNAMIC BLACK

1-GR-DC-TWO-2-DB-230



TOTAL BLACK

1-GR-DC-TWO-2-Y-230



DYNAMIC DARK

1-GR-DC-TWO-2-DD-230



TOTAL DARK

1-GR-DC-TWO-2-TD-230



DC SYSTEM



CUSTOM COLOURS



CUSTOM MATERIALS



HANDS FREE



FLAT BURRS



65mm BURRS